



**睿珀机电**  
SHANGHAI AGRIPOWER

## Diesel generating set

### AG-400P/S

400V/50Hz Main power//Perkins 2206C-E13TAG3



ISO14001:2015

ISO9001 :2015

OHSAS 18001:2007

#### Product features

##### Operative norm:

- ISO 8528:AC generator set driven by reciprocating internal combustion engine
- IEC 60034-1:Basic technical requirements for rotating motors
- YD/T 502: Communication diesel generator set
- GB/T 20136-2006 General test method for internal combustion engine power stations

##### Merit:

1. Integrated building block structure design, small volume, compact structure, sophisticated technology;
2. Few parts, light weight, low failure rate and low maintenance cost;
3. Supercharging and supercharging intercooling technology as the leading products, strong power;
4. High-performance damping system and rigid base, small vibration;
5. Efficient fuel supply system and air intake system, fuel atomization and air mixing more fully, more complete combustion, lower emissions;
6. Standardized design, comprehensive and intelligent products, parts and components have strong versatility, easy installation and easy maintenance;
7. maintenance-free battery, with fast start performance;



## Technical parameters of the unit

### Generator set

Generator model:...	AG-400P/S	Main power(kW):...	320
Standby power(kW):...	352	unit capacity(kVA):...	400
Rated speed(rpm):...	1500	frequency(Hz):...	50
Rated voltage(V):...	400	Rated current(A):...	577
Power factor(cosφ):...	0.8(lag)	Wiring mode:...	3 phase 4 wire
		Minimum smoke pipe diameter	
Generator weight (kg)	4268	(mm)	1×φ124
Air intake(m³/min):...	588	Air exhaust(m³/min):...	563
Generator size(mm):...	4500L×1470W×2483H	Recommended base size(mm):...	3500L×1600W

## Unit performance index (G2)

Parameter		unit	Performance index
Frequency drop		%	≤3
Steady state frequency band		%	≤0.5
Relative frequency setting drop range		%	≥3.5
Relative frequency setting rise range		%	≥2.5
Transient frequency deviation	100% sudden power reduction	%	≤+10
	Surge power		≤-7
Frequency recovery time		s	≤3
Relative frequency tolerance band		%	2
Steady-state voltage deviation		%	≤±1
Voltage unbalance degree		%	1
Transient voltage deviation	100% sudden power reduction	%	≤+20
	Surge power		≤-15
Voltage recovery time		s	≤4
Voltage modulation		%	0.3
Relative voltage setting range		%	≤±5
Voltage setting rate of change		%/s	0.2~1
Telephone harmonic factor	THF	%	<2
Telephone influence factor	TIF	—	<50



## Engine technical parameters

### Engine

Manufacturer: Perkins  
Model: 2206C-E13TAG2  
Engine structure: four-stroke  
Number : 6/L  
Displacement:L 12.5  
Cylinder diameter:mm 130  
Stroke:mm 157  
Compression ratio: 16.1: 1  
Speed:rpm 1500  
Primary/standby power :kW 368/412  
Speed regulation mode: ECM  
Cooling method: closed water cooling  
Dry weight (engine only) : kg 1478

### Start the system

Starting rated power:kW 7.8  
Starting rated voltage:V DC24

### Fuel system

Fuel injection form: high pressure common rail  
Fuel return flow:L/min 3.5

### Fuel consumption

Engine output	L/h	g/kwh
100%	85	212.3
75%	65	206
50%	46	210
25%	22	214

### Intake system

Maximum allowable intake resistance (clean filter element) : kPa 3  
Intake air flow: m<sup>3</sup>/min 25.2

### Lubrication system

Total lubrication system capacity: L 41  
Maximum allowable oil temperature :°C 125

### Cooling system

Engine coolant volume: L 51.4  
Coolant flow: L/min 318

### Exhaust system

Maximum exhaust back pressure: kPa 10  
Exhaust flow: m<sup>3</sup>/min 72  
Exhaust temperature:°C 630


## Technical parameters of generator

### Dynamo

\*50Hz,AC400V,cosφ=0.8

MODEL	Rated power(kW)	Standby power(kW)	Mechanical efficiency(%)	Insulation/temperature rise	Class of protection	Weight(kg)
LEROYSOMER: T AL A47A	330	350	91.5	H/H	IP21	976

## Size and weight



★ The above figure is for reference only, the actual size and weight are subject to the final design drawing.

Model	Engine model	size (L×W×H) (mm)	Dry weight (kg)	Wet weight (kg)
AG-400P/S	2206C-E13TAG2	4500×1470×2483	4200	4268

## Special instructions

1. Main power (PRP) is the maximum power that the unit can run continuously with variable load under standard environment (atmospheric pressure, relative humidity, ambient temperature), and the overload of 10% is allowed to run for 1h every 12h.
2. Working conditions and power correction:
  - (1) Altitude:  $\leq 1000\text{m}$  ( $> 1000\text{m}$ ), need to do power correction; Power reduction by 10% per 1000m increase)
  - (2) Ambient temperature:  $40^{\circ}\text{C}$  (when  $> 40^{\circ}\text{C}$ , power correction is required)
  - (3) Relative humidity:  $\leq 60\%$
3. When the field use conditions of the diesel generator set do not meet the above conditions, the output power of the unit should be corrected, and the final correction coefficient, please refer to the detailed technical data of the corresponding engine and generator.